

HOLE TABLE			
SCREW	SYMBOL	DESCRIPTION	PAGE
	A	13/32" DIA. x 1-9/16" DEEP	2
	B	15/32" DIA. C'DRILL x 1/4" DEEP	2
#10-24 X 1-1/8" PHMS	C	1/4" DIA.	1
	D	1/2" DIA	1
#10-24 SEX BOLT	E	13/32" DIA	2

HORIZONTAL  
CENTERLINE  
OF EXIT DEVICE

INSIDE DOOR PREP

NOTES:

1. THIS TEMPLATE IS FOR USE ON DOORS THAT PREVIOUSLY HAVE BEEN PREPARED FOR PRECISION HARDWARE INC. CONCEALED VERTICAL ROD EXIT DEVICE SERIES FL-1800 USING TRIM 15, 17 OR 17C, OR IF THE DOOR PREVIOUSLY DID NOT HAVE TRIM. THE EXIT DEVICE MUST HAVE THE NIGHT LATCH FUNCTION OR BE CONVERTED TO THE NIGHT LATCH FUNCTION.
2. REVISE THE HOLE PATTERN IN THE DOOR TO THE HOLE PATTERN OF THIS TEMPLATE. IF THE EXISTING HOLES IN THE DOOR ARE LARGER THAN THOSE SHOWN THEY MAY BE USED IF THEY MEET THE EXIT DEVICE MANUFACTURER'S SPECIFICATIONS.
3. RE-INSTALL THE EXIT DEVICE ON THE DOOR USING HOLES E AND RE-INSTALL THE MOUNTING BRACKET/END CAP USING THE ORIGINAL HARDWARE.
4. REFER TO THE OMNILOCK QUICK ADAPTER EXIT TRIM INSTALLATION INSTRUCTION TO INSTALL THE OMNILOCK TRIM AND SECURE THE EXIT DEVICE TO THE DOOR.



